



Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Frame-In Kit	Reflector Trims — See Individual Reflector Trim Specification Sheets									
<b>1000P1</b>	Open Downlight								Enclosed Diffusers	Wall Washer
	Reflector	Cone	Satin Cone	Baffles	Basic White	Pinhole	Adjustable	Eyeball		
	<b>1045</b> <b>1046</b> <b>1046CD</b>	<b>1012</b> <b>1012NM</b> <b>1013</b> <b>1013NM</b> <b>1013CD</b> <b>1013BKNM</b> <b>1013CDNM</b> <b>1013BK</b> <b>1013WH</b>	<b>1008</b> <b>1008NM</b> <b>1010</b> <b>1010NM</b>	<b>1005</b> <b>1005NM</b> <b>1005BNM</b> <b>1005WH</b> <b>1076</b> <b>1076WH</b>	<b>1071</b>	<b>1011</b>	<b>1029</b> <b>1029NM</b> <b>1029BK</b> <b>1029BKNM</b> <b>1029CD</b> <b>1029CDNM</b> <b>1029CL</b> <b>1029CLNM</b> <b>1029GD</b> <b>1029GDNM</b> <b>1029BNM</b>	<b>1082</b> <b>1023</b> <b>1023WH</b>	<b>1021</b> <b>1024</b> <b>1078</b>	<b>1035</b> <b>1035WH</b> <b>1085</b>

PAR30 lamps do not require socket extender. Long neck PAR30 lamps are not compatible with the 1029 series trims.

### Features

- 1. Housing:** .026" galvanized steel. Access door for inspection of junction box.
- 2. Mounting Frame:** .036" (#20 ga.) galvanized steel. Accommodates all ceilings up to 1" thick. Four slots are positioned 90° apart to simplify alignment. Push-in/twist-out rotoclips hold reflector flush to ceiling.
- 3. Junction Box:** 4" X 3 1/2" X 2" (22 cu. in.) .063" (#14 ga.) galvanized steel. U.L. listed for maximum of 8 No. 12 ga. 75° C through branch circuit conductors (60° C end of run). Integral cable clamps permit attachment of non-metallic Romex® or armored cable without need of additional connectors.
- 4. Mounting Bars:** .059" (#16 ga.) galvanized steel. 13" long bars extend to 27", rotatable and lockable, with integral T-bar tabs. Attach to wood joist or T-bar ceilings without the need of accessories.
- 5. Socket:** Porcelain medium base; nickel plated screw shell. Pre-wired with #18 ga. SF1 leads to junction box.
- 6. Thermal Protector:** Meets NEC and UL requirements. Insulation must be kept 3" away from fixture sides and wiring compartments and must not be placed above fixture in a manner which will entrap heat. Located inside housing.

### Options & Accessories

- Mounting Bars:** **1964** - 20" set of (2)
- Plaster Ceiling Ring:** **1960** - 7/8" depth for wet plaster ceilings.
- Extra-Thick Ceiling Mounting Ring:** **1967B** - up to 2" thick ceilings.

### Labels

UL (Suitable for Damp Locations), I.B.E.W.

Romex® is a registered Trademark of General Cable Industries Inc.  
**US Patent No.'s.: 5,045,985**

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

**Lightolier** a Genlyte company www.lightolier.com  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2006 Genlyte Group LLC • H0906